

Data Sheet

Contactores industriales compacto 25 - 40A		HGCB		
Norma		IEC 60947-4		
Número de polos		3P		
Tipo		HGC25B	HGC32B	HGC40B
Tensión de aislamiento [Ui]	V	800	800	800
Tensión nominal de empleo [Ue]	V	690	690	690
Tensión nominal impulsional [Uimp]	kV	6	6	6
Frecuencia	Hz	50/60		
Tensión de control (Uc)	V	220V		
Corriente nominal Ith (AC1)	A	45	55	60
AC3	200 ~ 240 V	5.5/25	7.5/32	11/40
	380 ~ 440 V	11/25	15/32	18.5/40
	500 ~ 550 V	15/17	18.5/20	22/23
	660 ~ 690 V	4/6	7.5/9	7.5/9
	1,000 V	-	-	-
Vida útil	Eléctrica	120	120	120
	Mecánica	800	800	800
AC4	200 ~ 240 V	3.7/18	4.5/22	5.5/25
	380 ~ 440 V	5.5/13	7.5/17	11/24
	Vida útil eléctrica	3	3	3
Método de instalación	Tornillo y Carril DIN			
Contactos auxiliares				
Estándar	AC	1NO		
Dimensiones	mm	54x84x92		

