

# Data Sheet

Contactores industriales compacto 9 - 18A		HGCB		
Norma		IEC 60947-4		
Número de polos		3P		
<b>Tipo</b>		<b>HGC9B</b>	<b>HGC12B</b>	<b>HGC18B</b>
Tensión de aislamiento [Ui]	V	800	800	800
Tensión nominal de empleo [Ue]	V	690	690	690
Tensión nominal impulsional [Uimp]	kV	6	6	6
Frecuencia	Hz	50/60		
Tensión de control (Uc)	V	220V		
Corriente nominal Ith (AC1)	A	25	30	40
AC3	200 ~ 240 V	2.5/9	3.5/12	4.5/18
	380 ~ 440 V	4/9	5.5/12	7.5/18
	500 ~ 550 V	4/7	7.5/12	8.5/13
	660 ~ 690 V	4/6	7.5/9	7.5/9
	1,000 V	-	-	-
	Vida útil	x10,000	140	140
	Eléctrica	1,000	1,000	1,000
	Mecánica	1,000	1,000	1,000
AC4	200 ~ 240 V	1.5/8	2.2/11	3.7/16
	380 ~ 440 V	2.2/6	4/9	4/11
	Vida útil eléctrica	x10,000	3	3
Método de instalación		Tornillo y Carril DIN		
Contactos auxiliares				
Estándar	AC	1NA		



## Medidas

